

## STANDING RIGGING

O'DAY 222

Z Spar

TITLE	SIZE/ CONST	PCL	FITTING A	FITTING B	EXTRA
Headstay	1/8	24'5"	Der T	7854-4-8-8	
Backstay	1/8	29'2 1/4"	Stemball 9 x 19 cup	7854-4-8-8	
Pendant	1/8	1'3 1/2"	AN667-4	14TJRT-1/8	SK 2881 in B; NOT IN PCL
Cap	1/8	23'3"	Der T	7854-4-8-8	
Lower	1/8	12'1 1/4"	Der T	7854-4-8-8	
T Lift	1/8 LL	24'4 1/2"	Stemball 9 x 19 cup	AN668-4 02-04	
TO END OF STUD					
Headstay	1/8	23'11"	Der T	5850-1032	
Backstay	1/8	28'8 1/8"	Stemball	5850-1032	
Cap	1/8	22'8 7/8"	Der T	5850-1032	
Lower	1/8	11'7"	Der T	5850-1032	

11-18-86

# RUNNING RIGGING

O'DAY 222

Z Spar

TITLE	SIZE	TYPE	LENGTH	A END	B END	EXTRA INFO
Jib Halyard	5/16	XLS-Blue	44'	93-42	Burn	
Main Halyard	5/16	XLS-Red	57'	93-42	Burn	
Main Sheet	3/8	TRO-Red	42'	SK4838 Spliced In	Whip	
Jib Sheet	3/8	TRO-Blue	35'	Whip	Whip	One
Reef	1/4	TRO-Green	21'6"	Burn	Burn	
Outhaul	1/4	XLS-POE	13'	Burn	Burn	
Topping Lift	1/4	XLS-POE	15'6"	Eye	Burn	

Specifications beginning with Hull No. 691

11-18-86

O'DAY 222  
STANDARD BOAT DIMENSIONS

HULL DIMENSIONS

LOA	21'9"	
LWL	19'7"	
BEAM	7'11"	
DRAFT	1'8"	Board Up
	4'8"	Board Down
DISPLACEMENT	2,200 Lbs.	
BALLAST	800 Lbs.	

RIG DIMENSIONS

I	22'9"
J	7'9"
P	23'9"
E	10'

SAIL AREA 207 Sq. Ft.

MISCELLANEOUS

Berths	4	
Fresh Water	5	Gallons
Fuel Capacity (Tank Bin Will Hold)	6	Gallon Tank (Not Included)
Engine Recommended HP	6 - 8	
Icebox Capacity	48	Qt. Cooler (Optional)

11-13-86