



DuPont™ Silicone Lubricant with Teflon™ fluoropolymer - Liquid

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Not applicable.
CAS No.	Mixture
Trade Name	DuPont™ Silicone Lubricant with Teflon™ fluoropolymer - Liquid
Product Code	None

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Lubricant
Uses Advised Against	None

Company Identification	Finish Line Technologies, Inc. 50 Wireless Blvd. Hauppauge, NY 11788
------------------------	--

Telephone	(631) 666-7300
E-Mail (competent person)	SDSinfo@finishlineusa.com

Emergency telephone number

Emergency Phone No.	Medical Emergency: PROSAR 24 hr: 1-800-217-5157 / 1-651-523-0304
---------------------	---

Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)	Flam. Liq. 2; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1
-----------------------------	---

Label elements

Hazard Symbol



DANGER

Hazard Statement(s)	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.
---------------------	---

Precautionary Statement(s)	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Wash hands and exposed skin thoroughly after handling: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Keep out of reach of children.
----------------------------	---

Other hazards

None



DuPont™ Silicone Lubricant with Teflon™ fluoropolymer - Liquid

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt.	CAS No.
Heptane, branched, cyclic and linear	20 - 30	426260-76-6
Distillates (petroleum), hydrotreated light	20 - 30	64742-47-8
Distillates (petroleum), blend of various solvent-refined and hydrotreated heavy paraffinic and residual oils	1 - 20	mixture

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms occur obtain medical attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways. Will cause skin irritation. Vapours may cause drowsiness and dizziness.

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.

-Unsuitable Extinguishing Media

Do not use water jet.

Special hazards arising from the substance or mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes.

Environmental precautions

Prevent liquid entering sewers, basements and workpits.



DuPont™ Silicone Lubricant with Teflon™ fluoropolymer - Liquid

Methods and material for containment and cleaning up Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections None
Additional Information None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.

Conditions for safe storage, including any incompatibilities

-Storage temperature Keep in a cool, well ventilated place.
 -Incompatible materials This product should be stored away from sources of strong heat or oxidising chemicals.

Specific end use(s) Lubricant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		STEL		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Heptane, branched, cyclic and linear	426260-76-6	500 ppm*	1500 mg/m ³	-----	-----	*n-heptane
Oil mist (mineral)	-----	5 mg/m ³	5 mg/m ³ ⁽¹⁾	-----	-----	⁽¹⁾ Inhalable

Recommended monitoring method NIOSH 1500 (hydrocarbons, B.P. 36 - 216 °C) ; NIOSH 5026 (Oil mist; mineral)

Exposure controls

Appropriate engineering controls Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other) Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)



Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.



Thermal hazards Not normally required.

Environmental Exposure Controls None known



DuPont™ Silicone Lubricant with Teflon™ fluoropolymer - Liquid

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Liquid
Color	Colourless
Odor	Petroleum spirit
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	94 - 98 (201 - 208 °F)
Flash Point (°C)	-8 (18 °F)
Evaporation Rate	Not available
Flammability (solid, gas)	Not applicable
Explosive Limit Ranges	Not available
Vapour pressure (Pascal)	Not available
Vapour Density (Air=1)	Not available
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (cSt)	<20 @ 40 °C
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	none

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	Strong oxidising agents
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Acrid smoke, Other

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Acute toxicity	Oral: LD50 >5 g/kg-bw Dermal: LD50 >2 g/kg-bw Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Irritation/Corrosivity	Causes skin irritation. Repeated exposure may cause skin dryness or cracking. Causes eye irritation.
Sensitization	It is not a skin sensitizer.
Repeated dose toxicity	NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects) LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects) May cause drowsiness or dizziness.
Carcinogenicity	No data. It is unlikely to present a carcinogenic hazard to man.



DuPont™ Silicone Lubricant with Teflon™ fluoropolymer - Liquid

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity
Toxicity for reproduction

There is no evidence of mutagenic potential.
No information available

SECTION 12: ECOLOGICAL INFORMATION

Toxicity - Substances in preparations / mixtures

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term	LL50 (96 hour): >13.4 mg/L (<i>Oncorhynchus mykiss</i>) EL50 (48 hour): 3 mg/l (<i>Daphnia magna</i> , mobility) EC50 (96 hour): 13 mg/l (<i>Pseudokirchnerella subcapitata</i>)
Long Term	NOELR (28 days) 1.5 mg/l (<i>Fish</i>) QSAR LOEC (21 days): 0.32 mg/l (<i>Daphnia magna</i>) NOEL (96 hour) 6.3 mg/l (<i>Algae</i>)
Persistence and degradability	Not available.
Bioaccumulative potential	Not available.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
-------------------------	--

SECTION 14: TRANSPORT INFORMATION

	Land transport (U.S. DOT)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN number	1206	1206	1206
Proper Shipping Name	Heptanes mixture	Heptanes mixture	Heptanes mixture
Transport hazard class(es)	3	3	3
Packing group	II	II	II
Environmental hazards	No.	No.	No.
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None	----	----	----

SARA 311/312 - Hazard Categories:



DuPont™ Silicone Lubricant with Teflon™ fluoropolymer - Liquid

Fire Sudden Release Reactivity Immediate (acute) Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
None	----	----

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None	----	----

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.