

STANDING RIGGING

QTY	Description	Wire size & Type	Fitting to Fitting	
1	Headstay	1/4" - 1X19	M.EYE / 8-16	39' 2"
1	Upper Backstay	1/4" - 1X19	M.EYE / JAW	30'
2	Lower Backstay	3/16" - 1X19	JAW / 6-12-12	9' 10 1/4"
2	Upper Uppers	3/16" - 1X19	M.EYE / A+N EYE	10' 8 5/8"
2	Lower Uppers	3/16" - 1X19	A+N EYE / 6-12-12	25' 6"
2	Upper Intermediates	3/16" - 1X19	M. EYE / A+N EYE	11' 6"

RUNNING RIGGING

QTY	Description	SIZE	OTHER INFO AND SHACKLE	LENGTH IN FEET
			EYE W/3900	
1	MAIN HALYARD	3/8" XLS	SHACKLE B.E.	90
1	JIB HALYARD	7/16" XLS	EYE W/721-2	98
1	MAIN SHEET	3/8" XLS	B.B.E	68
2	JIB SHEETS	7/16" XLS	B.B.E	40
1	VANG	7/16" XLS	B.B.E	35
	TRAVELER CONTROL	3/8" XLS		
1	LINE		B.B.E	20
1	OUTHAUL	5/32" 7X19 SS	THIM. - OPEN	10
		3/16" XLS	B.B.E	28
1	CUNNINGHAM	1/4" XLS	EYE W/721-1	28
1	TOPPING LIFT	5/16" XLS	B.B.E	70
2	REEF LINES	5/16" XLS	B.B.E	16
1	JIFFY REEF	1/4" XLS	B.B.E	50
			EYE W/3900	
1	MAIN HALYARD	3/8" XLS	SHACKLE B.E.	90
1	JIB HALYARD	7/16" XLS	EYE W/721-2	98