


Polypropylene and Rubber Draw Latches



Made for light duty applications, these latches have nonmetal bodies to resist corrosion. Latch distance is fixed. Mounting screws are not included. **Polypropylene** latches have a temperature range of 32° to 150° F. **Rubber** latches absorb vibration and compensate for misalignment. Temperature range is -20° to +120° F.

Latch Distance	Overall Size*			Screw Size	Max. Padlock Shackle Dia.	Color	Pkg. Qty.		
	Lg.	Wd.	Proj.						
<b>Nonlocking— Polypropylene</b>									
<b>M</b> 25/32"	1 3/4"	45/64"	1/4"	#2	—	Black	10	<a href="#">1891A48</a>	\$9.66
<b>M</b> 1 3/64"	2 5/32"	1 13/64"	5/16"	#4	—	Black	10	<a href="#">1891A49</a>	12.41
<b>Nonlocking— Rubber</b>									
<b>N</b> 1 35/64"	4 3/32"	1 1/4"	49/64"	#8	—	Black	—	<a href="#">1070A79</a>	<b>Each</b> \$13.86
<b>N</b> 1 63/64"	4 5/32"	1 1/4"	49/64"	#8	—	Black	—	<a href="#">1070A81</a>	12.93
<b>N</b> 3 63/64"	6 29/64"	1 51/64"	1 5/32"	#10	—	Black	—	<a href="#">1070A82</a>	20.75
<b>Padlockable— Rubber</b>									
<b>N</b> 1 63/64"	4 5/32"	1 1/4"	29/32"	#8	5/16"	Black	—	<b><a href="#">1070A91</a></b>	14.32

\* Overall length includes strike.