

## INSTALLATION INSTRUCTIONS

# O'day

## Mast Tabernacle for Javelin and Day Sailer

READ THESE INSTRUCTIONS THOROUGHLY  
BEFORE INSTALLING YOUR MAST TABERNACLE

### KIT CONTENTS:

1- Tabernacle -	#52168 (Day Sailer)
	#52151 (Javelin)
6- 1/2" 10-24 PH/SS/MS	#60424
6- 10-24 locknuts -	#60136
1 Pin	#22110

### INSTRUCTIONS:

1. On Day Sailer, remove the halyard cleats  
On Javelin, remove the two halyard cleats
2. Mark two lines around the mast in the following locations:  
Javelin - 28" and 29.5" from the bottom of Mast.  
Day Sailer II - 26.5" and 28" from bottom of Mast.  
Day Sailer I - 32.5" and 34" from bottom of mast.
3. Cut carefully on both lines, using a fine-toothed Hacksaw. Clean up burr inside both pieces with a round file.
4. Attach either half of tabernacle to the bottom section with 3 10-24 Screws (see photos).
5. Attach other half of tabernacle to mast.  
On the Day Sailer, re-install the halyard cleats. On Javelin, re-install cleats as shown. (Use 1/8" drill).
6. Put mast step on bottom of mast. Use a 1/4" drill bit, drill a hole through the mast and step. Remove the step and place it back on the boat.
7. To raise mast, remove forward tabernacle pin, insert stub in boat and seat bottom of mast on mast step. Insert pin through the mast and step. This will keep it from rising when you are raising or lowering the mast. Making sure that all rigging is clear, fasten shrouds to chainplates. Using the hinge thus formed, raise the mast and insert the pin as shown. Insert circular cotter pin to keep pin in place. Fasten forestay and tension stays properly. It is not necessary to remove the sidestays to lower mast.

**CAUTION:** When lowering and raising mast, be sure not to twist spar, as it may cause damage to the mast and tabernacle.

