

SPECS FOR HUNTER 34 STANDING RIGGING

- 1 Headstay 9/32" 1x19 Wire Marine Eye to Turnbuckle, Eye to Eye 48'4"
- 1 Backstay Upper 9/32" 1x19 Wire Jaw to Marine Eye, Eye to Eye 36'6.5"
- 2 Lower Backstay Legs 1/4" 1x19 Wire Jaw to Turnbuckle, Eye to Eye 13'11.5"
- 2 Upper Upper Legs 1/4" 1x19 Wire Marine Eye to Marine Eye, Eye to Eye 12'6"
- 2 Upper Lower Legs 1/4" 1x19 Wire Marine Eye to Turnbuckle, Eye to Eye 33'6"
- 2 Intermediate Upper Leg 1/4" 1x19 Wire Marine Eye to Marine Eye, Eye to Eye 14'10.5"
- 2 Intermediate Lower Leg 1/4" 1x19 Wire Marine Eye to Turnbuckle, Eye to Eye 18'2"
- 2 Lower Shrouds 9/32" 1x19 Wire Marine Eye to Turnbuckle, Eye to Eye 17'6"
- 2 Intermediate Diamond Shrouds 1/4" 1x19 Wire Marine Eye to Turnbuckle, w/U removed Eye to Eye 15'7-7/8"
- 2 Lower Diamond Shrouds 1/4" 1x19 Wire Marine Eye to Turnbuckle, w/U removed Eye to Eye 16'5"

SPECS FOR HUNTER 34 RUNNING RIGGING

- 1 Main Halyard 7/16" XLS Splice on MH Shackle 110'
- 1 Jib Halyard 7/16" XLS Splice on NF Shackle 110'
- 1 Main Sheet 7/16" Yacht Braid 60'
- 1 Genoa Sheet 7/16" Yacht Braid 100'
- 1 Spinnaker Sheet 7/16" Yacht Braid 100'
- 1 Traveler Line 3/8" Yacht Braid. 40'
- 1 Vang Line 3/8" Yacht Braid 50'
- 1 Topping Lift 1/8" 7x7 PVC Thimble to Thimble 44'
- 2 Reefing lines through boom 3/8" XLS 45' & 60'

TENSION ON SHROUDS

TENSION	Shroud Diameter	Ft/ lbs	LOOS SCALE
Lower Shroud	9/32"	1200	46/47
Middle & Upper Shrouds	1/4"	1060	40/41
Forestay	9/32"	1200	46/47
Backstay	9/32"	1200	46/47
Backstay / 2	1/4"	1060	40/41